

FILE SHIGAJP5.DOC
4/14/06 CSP

37/7/4 (Item 4 from file: 347)
DIALOG(R)File 347:JAPIO
(c) 2006 JPO & JAPIO. All rts. reserv.

07930973
FOAMING ADHESIVE COMPOSITION

PUB. NO.: 2004-043732 [JP 2004043732 A]
PUBLISHED: February 12, 2004 (20040212)
INVENTOR(s): TAKAMATSU YORINOBU
FUJITA ATSUSHI
APPLICANT(s): THREE M INNOVATIVE PROPERTIES CO
APPL. NO.: 2002-205938 [JP 2002205938]
FILED: July 15, 2002 (20020715)

ABSTRACT

PROBLEM TO BE SOLVED: To obtain a foaming adhesive composition, which is excellent in heat resistance before foaming treatment and can easily be peeled off from an adhering subject after foaming treatment.

SOLUTION: This composition comprises an adhesive polymer, a foaming ingredient containing a t-butyloxycarbonyl structure and a foaming initiator.

COPYRIGHT: (C)2004,JPO

38/7/4 (Item 4 from file: 351)
DIALOG(R)File 351:Derwent WPI
(c) 2006 Thomson Derwent. All rts. reserv.

016201250 **Image available**
WPI Acc No: 2004-359136/*200434*

Foamable adhesive-agent composition for tapes or films of adhesive sheets, comprises adhesive polymer, foamable component having t-butyloxy carbonyl structure, and foam initiator

Patent Assignee: 3M INNOVATIVE PROPERTIES CO (MINN)

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Week
JP 2004043732	A	20040212	JP 2002205938	A	20020715	200434
						B

Priority Applications (No Type Date): JP 2002205938 A 20020715

Patent Details:

Patent No	Kind	Lan	Pg	Main IPC	Filing Notes
JP 2004043732	A		19	C09J-201/00	

Abstract (Basic): *JP 2004043732* A

NOVELTY - A foamable adhesive-agent composition comprises an adhesive polymer, a foamable component having a t-butyloxy carbonyl structure (1), and a foam initiator.

DETAILED DESCRIPTION - A foamable adhesive-agent composition

comprises an adhesive polymer, a foamable component having a t-butyloxy carbonyl structure of formula (1), and a foam initiator.

USE - For tapes or films of adhesive sheets used for temporary fixing in assembly processes of painting masking sheets, electronic components, protective films, semiconductor-wafer manufacture, and printed wiring boards.

ADVANTAGE - The foamable adhesive-agents composition has excellent heat resistance, and is easily peeled from an adherend.

pp; 19 DwgNo 0/0

Derwent Class: A81; G03

International Patent Class (Main): C09J-201/00

International Patent Class (Additional): C09J-004/00; C09J-133/06;
C09J-163/00